

# Using SQLMY

## Contents

- Overview ..... 2
- Prerequisites ..... 2
- A Database Must Exist in the Running Instance of MySql: ..... 3
- Actions..... 5
  - BeginTransaction ..... 5
  - Clear ..... 6
  - Close..... 6
  - CommitTransaction..... 6
  - Count ..... 8
  - Create ..... 8
  - DateFormat..... 9
  - DBNull..... 10
  - DecimalSeparator ..... 10
  - Delete ..... 11
  - Exec..... 11
  - ExecDeleteQuery..... 12
  - ExecInsertQuery ..... 13
  - ExecSelectQuery ..... 15
  - ExecStoredProc..... 16
  - ExecStoredProcCmd ..... 18
  - GetAllRecords..... 18
  - GetConnectionState ..... 19
  - GetConnectionString..... 20
  - GetRecord ..... 21
  - GroupSeparator ..... 21
  - ? or Help ..... 22
- Instances ..... 23
- InTransaction ..... 23
- New..... 24

|                                       |    |
|---------------------------------------|----|
| Open.....                             | 24 |
| RegionalSettings.....                 | 25 |
| RollbackTransaction .....             | 25 |
| Self.....                             | 27 |
| Learn Structured Query Language ..... | 28 |

## Overview

The APL64 `SQLMY` system function provides a structured query language (SQL)-based interface to a MySQL database.

The `SQLMY` system function employs the Oracle MySQL.Data Nuget package for a MySQL .Net client in APL64. The object model for `SQLMY` includes methods and properties to easily create a secure, high-performance application system data interface.

```

0  SQLMY '?'
1  SQLMY Summary Documentation
2      instanceName SQLMY 'BeginTransaction'
3      '#'          SQLMY 'Clear'
4      instanceName SQLMY 'Close'
5      instanceName SQLMY 'CommitTransaction'
6 char[]          +-instanceName SQLMY 'GetConnectionState'
7 connString     +-instanceName SQLMY 'GetConnectionString'
8 Int32          +-#'          SQLMY 'Count'
9 instanceName   +-#'          SQLMY 'Create' instanceName
10 dateFormat    +-instanceName SQLMY 'DateFormat'
11 decimalSeparator +-instanceName SQLMY 'DecimalSeparator'
12              instanceName SQLMY 'Delete'
13 Int32(rcdSetId) +-instanceName SQLMY 'Exec cmdText(Not a query)'
14 Int32         +-instanceName SQLMY 'ExecDeleteQuery' cmdText
15              instanceName SQLMY 'ExecInsertQuery' tableName fieldNames data
16 Int32(rcdSetId) +-instanceName SQLMY 'ExecSelectQuery' cmdText
17 matrix of values +-instanceName SQLMY 'ExecStoredProc' cmdText fieldNames dataVector
18 matrix of values +-instanceName SQLMY 'ExecStoredProcCmd' cmdText
19 matrix of values +-instanceName SQLMY 'GetAllRecords Int32(rcdSetId)'
20 vector of values +-instanceName SQLMY 'GetRecord Int32(rcdSetId)'
21 groupSeparator +-instanceName SQLMY 'GroupSeparator'
22 charVec       +-#'          SQLMY '?'
23 charVec       +-#'          SQLMY 'Help'
24 vector of char vectors+ '#'  SQLMY 'Instances'
25 bool          +-instanceName SQLMY 'InTransaction'
26 charVec       +-instanceName SQLMY 'New'
27              instanceName SQLMY 'Open' connString
28              instanceName SQLMY 'RegionalSettings' dateFormat decimalSeparator numberGroup
29              instanceName SQLMY 'RollbackTransaction'
30 charVec       +-instanceName SQLMY 'Self'
31
32

```

The [MySQL Community Edition](#) database is available as a no-cost option.

## Prerequisites


To use `SQLMY`, the MySQL database engine must be installed and running on the target workstation or on a server to which the target workstation has access.

## A Database Must Exist in the Running Instance of MySQL:

A database must exist on the target workstation or on a server to which the target workstation has access. The [MySQL Workbench](#) is an excellent tool to establish this instance.

The examples in this document are for demonstration purposes, so they may not incorporate enterprise-level security measures, use a local workstation deployment not amenable to sharing data, and use a simplified [connection string](#). For simplicity, some examples do not include all APL64 executable statements which may be necessary to reproduce the illustrated output. Some of the output from the examples was generated from multi-row APL64 executable statements.

The examples in the remainder of this document are based on the sample database, tables and values illustrated here. The database name (schema) is 'schema1' and the table in the database is 'tbone' which can be created using the MySQL Workbench:




Insert the tbone table sample data:

```
insert into tbone values (1,'Joe','1960-01-01',50000);  
insert into tbone values (2,'Jim','1961-01-01',60000);
```

Create the sample stored procedure with arguments and results:


```
CREATE PROCEDURE `spGetCompensationFromName`  
(IN NameMatch VARCHAR(45), OUT COMP DOUBLE)  
BEGIN
```

```
SELECT Compensation INTO COMP FROM tbone WHERE Name=NameMatch;
END
```



Create the sample stored procedure without arguments or results:

```
CREATE PROCEDURE `StoredProc1`
()
BEGIN
insert into tbone values (3,'Salmon','1950-02-01',150000);
END
```



## Actions

MySQL actions operate on either the `SQLMY` object or an `SQLMY` instance. The `SQLMY` object is a container for all `SQLMY` instances in an APL64 instance. An `SQLMY` instance is associated with a specific MySQL database accessible to the target workstation user.

The left argument of the APL64 `SQLMY` system function determines if the `SQLMY` action applies to the `SQLMY` object ('#' left argument) or `SQLMY` instance (name of `SQLMY` instance).

The name of an `SQLMY` instance can be specified by:

- An APL64 text expression, e.g. 'myinstance', «myinstance»
- An APL64 variable with value equal to an `SQLMY` instance name
- Elided, if the `SQLMYSelf` value is an `SQLMY` instance name


`SQLMY` action names are not case sensitive. `SQLMY` instance names are case sensitive.

## BeginTransaction

This action applies to an `SQLMY` instance. The `BeginTransaction` action, for the MySQL instance named in the left argument, indicates that subsequent `SQLMY` actions will be incorporated into an SQL transaction. An SQL transaction may contain multiple `SQLMY` actions. An SQL transaction can either be committed or rolled back. The `BeginTransaction` action has no result.

[SQL transactions](#) are used to combine multiple SQL statements, possibly affecting multiple tables in an SQL database, so that they are either all performed or none are performed.

```
SQLMYSelf←'#'SQLMY 'Create' 'S1'  
cstr←"server=localhost;port=3306;database=schema1;userid=root;password=Ezalb"  
SQLMY 'Open' cstr  
SQLMY 'BeginTransaction'  
SQLMY 'InTransaction'
```



The screenshot shows the APL64: CLEAR WS window with a menu bar (File, Edit, Session, Objects, Tools, Options, Help) and a toolbar. The main text area contains the following code:


```
0 SQLMYSelf+'#'SQLMY 'Create' 'S1'  
1 cstr+'server=localhost;port=3306;database=schema1;userid=root;password=Ezalb"  
2 SQLMY 'Open' cstr  
3 SQLMY 'BeginTransaction'  
4 SQLMY 'InTransaction'  
5 1  
6 |
```

The status bar at the bottom indicates "Ready" and "Hist: Ln: 6 Col: 6 | Ins | Classic | Num | EN\_US".

## Clear

This action is performed on the `SQLMY` object. The Clear action closes the MySQL database connection associated with any `SQLMY` instance and deletes all `SQLMY` instances in the current APL64 instance. The Clear action has no result.


```
S←'#' SQLMY'Create' 'S'  
'#' SQLMY'Instances'  
'#' SQLMY'Clear'  
'#' SQLMY'Instances'
```



## Close

The close action is performed on an `SQLMY` instance. The close action will close an existing connection and delete the associated `SQLMY` instance.

```
S←'#' SQLMY'Create' 'DBInst1'  
'DBInst1' SQLMY'Close'  
'#' SQLMY'Count'
```



## CommitTransaction


This action applies to an `SQLMY` instance. The CommitTransaction action causes the effects of the current transaction to be applied to the connected MySQL database. The CommitTransaction action has no effect if the BeginTransaction action has not occurred or if the RollbackTransaction action has occurred.

Prior to committal or rollback of a transaction, the effects of the existing SQL statements in the transaction are pending effects in the MySQL database. The CommitTransaction action has no result.

```

 sqlmyself←'#' sqlmy 'Create' 'S1'
cstr←"server=localhost;port=3306;database=schema1;userid=root;password=Ezalb"
 SQLMY 'Open' cstr
 SQLMY 'CommitTransaction'

```



```

 sqlmyself←'#' sqlmy 'Create' 'S1'
cstr←"server=localhost;port=3306;database=schema1;userid=root;password=Ezalb"
 sqlmy 'Open' cstr
 SQLMY 'ExecSelectQuery' 'Select Name from tbone;'
 SQLMY 'GetAllRecords' 102
 SQLMY 'BeginTransaction'
 SQLMY 'ExecInsertQuery' 'tbone' 'Id,Name,DOB,Compensation' (3 'Salmon' '1966-01-01' 90500.56)
 SQLMY 'ExecSelectQuery' 'Select Name from tbone;'
 SQLMY 'GetAllRecords' 103
 SQLMY 'CommitTransaction'
 SQLMY 'ExecSelectQuery' 'Select Name from tbone;'
 SQLMY 'GetAllRecords' 104
 SQLMY 'ExecDeleteQuery' 'Delete From tbone Where Id=3;'


```

Note that the records in the #103 data set include the pending effects of the ExecInsertQuery action and the records in the #104 data set include the effects of the committed ExecInsertQuery action:



The Create action will not fail if the named instance already exists. The Create action will close and delete a pre-existing instance with the same name. The Create action for a particular MySQL database is generally used once in an APL64 instance. The Create action does not open a connection to an MySQL database, use the Open action for that purpose. The result of a successful 'Create' action is a text vector containing the SQLMY instance name.

```
'#'SQLMY 'Clear'  
'ρ'←'#'SQLMY 'count'  
'#'SQLMY 'Create' 'A'  
'#'SQLMY 'Create' 'B'  
'#'SQLMY 'Instances'  
'ρ'←'#'SQLMY 'count'
```



### DateFormat

This action returns the current [.Net Short Date Pattern](#) text applicable to the specified SQLMY instance.

```
SQLMYSelf←'#'SQLMY 'Create' 'S'  
SQLMY 'DateFormat'  
SQLMY 'DecimalSeparator'  
SQLMY 'GroupSeparator'
```

```

0      □SQLMYSelf←'#'□SQLMY 'Create' 'S'
1      □SQLMY 'DateFormat'
2      M/d/yyyy
3      □SQLMY 'DecimalSeparator'
4      .
5      □SQLMY 'GroupSeparator'
6      ,
7

```

### DBNull

This action returns a value which may be used to specify null values for the ExecInsertQuery and ExecStoredProc □SQLMY instance actions. This value will also be used as the APL64 value associated with a DBNull value returned from a GetRecord, GetAllRecords, or ExecStoredProc action.

```

□←DBNull←'#'□SqlMy 'DBNull'
DBNull≡1 1ρ«DBNull»

```

```

0      □←DBNull←'#'□SqlMy 'DBNull'
1      DBNull
2      DBNull≡1 1ρ«DBNull»
3      1
4

```

### DecimalSeparator

This action returns the current [.Net Number Decimal Separator](#) text applicable to the specified □SQLMY instance.

```

□SQLMYSelf←'#'□SQLMY 'Create' 'S'
□SQLMY 'DateFormat'
□SQLMY 'DecimalSeparator'
□SQLMY 'GroupSeparator'

```

```

0      □SQLMYSelf←'#'□SQLMY 'Create' 'S'
1      □SQLMY 'DateFormat'
2      M/d/yyyy
3      □SQLMY 'DecimalSeparator'
4      .
5      □SQLMY 'GroupSeparator'
6      ,
7

```

### Delete

The Delete action is performed on an □SQLMY instance. The close action will close an existing connection and delete the associated □SQLMY instance.

```

'#' □SQLMY'Clear'
S←'#' □SQLMY'Create' 'DBInst1'
'#' □SQLMY'Count'
'DBInst1' □SQLMY 'Delete'
'#' □SQLMY'Count'

```

```

0      '#' □SQLMY'Clear'
1      S←'#' □SQLMY'Create' 'DBInst1'
2      '#' □SQLMY'Count'
3      'DBInst1' □SQLMY 'Delete'
4      '#' □SQLMY'Count'
5      1
6      0
7

```

### Exec

This action applies to an □SQLMY instance. The □SQLMY Exec action returns the number of database rows, if any, affected by the executed SQL statement provided by the right argument. The □SQLMY Exec action cannot be used to return results of a Select SQL statement.

```


□sqlmyself←'#'□sqlmy 'Create' 'S1'
cstr←"server=localhost;port=3306;database=schema1;userid=root;password=Ezalb"

```

```

 sqlmy 'Open' cstr
 SQLMY 'Exec' "Insert Into tbone (Id,Name,DOB,Compensation) VALUES (3,'Salmon','1966-01-01',90500.56);"
 SQLMY 'ExecSelectQuery' 'Select Id, Name, DOB, Compensation From tbone;'
 SQLMY 'GetAllRecords' 102
 SQLMY 'Exec' 'Delete From tbone Where Id=3;'

```



### ExecDeleteQuery

This action applies to an SQLMY instance. The right argument is the text of the SQL Delete statement. The result of the SQLMY ExecDeleteQuery is the number of records affected, if any.

```

 sqlmyself←'#'□sqlmy 'Create' 'S1'
cstr←"server=localhost;port=3306;database=schema1;userid=root;password=Ezalb"
 sqlmy 'Open' cstr
 SQLMY 'Exec' "Insert Into tbone (Id,Name,DOB,Compensation) VALUES (3,'Salmon','1966-01-01',90500.56);"
 SQLMY 'ExecSelectQuery' 'Select Id, Name, DOB, Compensation From tbone;'
 SQLMY 'GetAllRecords' 102
 SQLMY 'ExecDeleteQuery' 'Delete From tbone Where Id=3;'
 SQLMY 'ExecSelectQuery' 'Select Id, Name, DOB, Compensation From tbone;'
 SQLMY 'GetAllRecords' 103

```

```

0  □sqlmyself←'#'□sqlmy 'Create' 'S1'
1  cstr←"server=localhost;port=3306;database=schema1;userid=root;password=Ezalb"
2  □sqlmy 'Open' cstr
3  □SQLMY 'Exec' "Insert Into tbone (Id,Name,DOB,Compensation) VALUES (3,'Salmon','1966-01-01',90500.56);"
4  □SQLMY 'ExecSelectQuery' 'Select Id, Name, DOB, Compensation From tbone;'
5  □SQLMY 'GetAllRecords' 102
6  □SQLMY 'ExecDeleteQuery' 'Delete From tbone Where Id=3;'
7  □SQLMY 'ExecSelectQuery' 'Select Id, Name, DOB, Compensation From tbone;'
8  □SQLMY 'GetAllRecords' 103
9  1
10 102
11 1 Joe    1/1/1960 12:00:00 AM 50000.00
12 2 Jim    1/1/1961 12:00:00 AM 60000.00
13 3 Salmon 1/1/1966 12:00:00 AM 90500.56
14 1
15 103
16 1 Joe 1/1/1960 12:00:00 AM 50000
17 2 Jim 1/1/1961 12:00:00 AM 60000
18

```

## ExecInsertQuery

This action applies to an SQLMY instance.

Right arguments:

1. MySQL table name
2. MySQL column names: Comma delimited text with selected MySQL table column names, or '\*' to indicate all MySQL table column names.
3. APL64 data: A matrix containing the APL64 values to be inserted. One row for each record to be inserted.

The order of the MySQL column names and APL64 data matrix columns must be conformable.

Specify all columns by name:

```

sqlmyself←'#'□sqlmy 'Create' 'S1'
cstr←"server=localhost;port=3306;database=schema1;userid=root;password=Ezalb"
sqlmy 'Open' cstr
SQLMY 'ExecInsertQuery' 'tbone' 'id,name,dob,compensation' (3 'Salmon' '1966-01-01' 90500.56)
SQLMY 'ExecSelectQuery' 'Select Id, Name, DOB, Compensation From tbone;'
SQLMY 'GetAllRecords' 102
SQLMY 'Exec' 'Delete From tbone Where Id=3;'

```

```

APL64: CLEAR WS
File Edit Session Objects Tools Options Help
[Icons]
0 □sqlmyself←'#'□sqlmy 'Create' 'S1'
1   cstr←"server=localhost;port=3306;database=schema1;userid=root;password=Ezalb"
2   □sqlmy 'Open' cstr
3   □SQLMY 'ExecInsertQuery' 'tbone' ' id,name,dob,compensation' (3 'Salmon' '1966-01-01' 90500.56)
4   □SQLMY 'ExecSelectQuery' 'Select Id, Name, DOB, Compensation From tbone;'
5   □SQLMY 'GetAllRecords' 102
6   □SQLMY 'Exec' 'Delete From tbone Where Id=3;'
7 102
8 1 Joe      1/1/1960 12:00:00 AM 50000.00
9 2 Jim      1/1/1961 12:00:00 AM 60000.00
10 3 Salmon  1/1/1966 12:00:00 AM 90500.56
11 1
12
Ready | Cmd: Ln: 0 Col: 0 Ins | Classic | Num | EN_US

```

If only certain (nullable) column values are to be inserted, the required values for the non-nullable columns must also be inserted. Database null values are converted to APL64: 0 0p0:

```

 sqlmyself←'#'□sqlmy 'Create' 'S1'
cstr←"server=localhost;port=3306;database=schema1;userid=root;password=Ezalb"
 sqlmy 'Open' cstr
 SQLMY 'ExecInsertQuery' 'tbone' ' Id,Name,Compensation' (3 'Salmon' 90500.56)
 SQLMY 'ExecSelectQuery' 'Select Id, Name, DOB, Compensation From tbone where Id=3;'
 SQLMY 'GetAllRecords' 102
 SQLMY 'Exec' 'Delete From tbone Where Id=3;'

```

```

APL64: CLEAR WS
File Edit Session Objects Tools Options Help
[Icons]
0 □sqlmyself←'#'□sqlmy 'Create' 'S1'
1   cstr←"server=localhost;port=3306;database=schema1;userid=root;password=Ezalb"
2   □sqlmy 'Open' cstr
3   □SQLMY 'ExecInsertQuery' 'tbone' ' Id,Name,Compensation' (3 'Salmon' 90500.56)
4   □SQLMY 'ExecSelectQuery' 'Select Id, Name, DOB, Compensation From tbone where Id=3;'
5   □SQLMY 'GetAllRecords' 102
6   □SQLMY 'Exec' 'Delete From tbone Where Id=3;'
7 102
8 3 Salmon      90500.56
9 1
10 |
Ready | Hist: Ln: 10 Col: 6 Ins | Classic | Num | EN_US

```

Specify all columns to be inserted with '\*':

```

 sqlmyself←'#'□sqlmy 'Create' 'S1'
cstr←"server=localhost;port=3306;database=schema1;userid=root;password=Ezalb"
 sqlmy 'Open' cstr
 SQLMY 'ExecInsertQuery' 'tbone' '*' (3 'Salmon' '1966-01-01' 90500.56)
 ↑ No column specification needed if data for all columns is provided
 SQLMY 'ExecSelectQuery' 'Select Id From tbone;'
 SQLMY 'GetAllRecords' 102
 SQLMY 'Exec' 'Delete From tbone where Id=3;'

```

```

APL64: CLEAR WS
File Edit Session Objects Tools Options Help
[Icons]
0  []sqlmyself←'#[]sqlmy 'Create' 'S1'
1  cstr←"server=localhost;port=3306;database=schema1;userid=root;password=Ezalb"
2  []sqlmy 'Open' cstr
3  []SQLMY 'ExecInsertQuery' 'tbone' '*' (3 'Salmon' '1966-01-01' 90500.56)
4  At No column specification needed if data for all columns is provided
5  []SQLMY 'ExecSelectQuery' 'Select Id From tbone;'
6  []SQLMY 'GetAllRecords' 102
7  []SQLMY 'Exec' 'Delete From tbone where Id=3;'
8  102
9  1
10 2
11 3
12 1
13
Ready | Hist: Ln: 13 Col: 6 | Ins | Classic | Num | EN_US

```

## ExecSelectQuery

The ExecSelectQuery action applies to an `[]sqlmy` instance. The action argument provides the SQL Select statement. Depending on the MySQL data type of a column selected, it may be necessary to cast that data column values to a data type which has a representation in APL64.

The ExecSelectQuery does not return the result of the SQL Select statement. The result is an integer indicating the record set containing the result of the SQL Select statement. Use the 'GetRecord' or 'GetAllRecords' actions to access the specified record set.

The SQL-format query text argument to the `[]SQLMY ExecSelectQuery` method, should yield only on record set. A query of the form 'query1;...;queryN', is not supported in APL64 and must be separated into individual queries. As an alternative to separate queries, a stored procedure can be created and executed using the `[]SQLMY ExecStoredProc` method.

```

[]sqlmyself←'#[]sqlmy 'Create' 'S1'
cstr←"server=localhost;port=3306;database=schema1;userid=root;password=Ezalb"
[]sqlmy 'Open' cstr
[]SQLMY 'ExecSelectQuery' "Select Name From tbone Where Id=2"
[]SQLMY 'GetRecord' 102

```

```

APL64: CLEAR WS
File Edit Session Objects Tools Options Help
[Icons]
0  []sqlmyself←'#[]sqlmy 'Create' 'S1'
1  cstr←"server=localhost;port=3306;database=schema1;userid=root;password=Ezalb"
2  []sqlmy 'Open' cstr
3  []SQLMY 'ExecSelectQuery' "Select Name From tbone Where Id=2"
4  []SQLMY 'GetRecord' 102
5  102
6  Jim
7
Ready | Hist: Ln: 7 Col: 6 | Ins | Classic | Num | EN_US

```

```

[]sqlmyself←'#[]sqlmy 'Create' 'S1'
cstr←"server=localhost;port=3306;database=schema1;userid=root;password=Ezalb"
[]sqlmy 'Open' cstr
sq←'Select Id,Name,DOB,Compensation From tbone;'
[]SQLMY 'ExecSelectQuery' sq
[]SQLMY 'GetAllRecords' 102

```

```

APL64: CLEAR WS
File Edit Session Objects Tools Options Help
0 []sqlmyself+'#[]sqlmy 'Create' 'S1'
1 cstr+"server=localhost;port=3306;database=schema1;userid=root;password=Ezalb"
2 []sqlmy 'Open' cstr
3 sq+'Select Id,Name,DOB,Compensation From tbone;'
4 []SQLMY 'ExecSelectQuery' sq
5 []SQLMY 'GetAllRecords' 102
6 102
7 1 Joe 1/1/1960 12:00:00 AM 50000
8 2 Jim 1/1/1961 12:00:00 AM 60000
9
Ready | Hist: Ln: 9 Col: 6 | Ins | Classic | Num | EN_US

```

## ExecStoredProc

This action can be used to run a stored procedure which is input, output and combined input/output parameters.

Syntax: MatrixOfValues←instanceName[]SqlMy 'ExecStoredProc' procName paramNames dataVector

The action arguments are:

- An APL text vector (procName) containing the stored procedure name.
- Comma-delimited APL text (paramNames) containing the stored procedure parameter names. Prefixed and suffixed space characters will be trimmed from each parameter name.
- An APL rank-1 vector(dataVector) of 'In' and 'InOut' parameter values. The order of the parameter values and the order of the 'In' and 'InOut' parameter names must be conformable. There should be no 'place holder' element in the dataVector for an Out parameter.

The parameter specifications, direction(In, InOut, Out) and data type, are determined by APL64 by querying the applicable database system tables.

Not all MySql data types can be represented in APL64, so the data types of stored procedure parameters must be carefully considered. For MySql data types which have no representation in APL64, the stored procedure must cast the parameter values to APL64-compatible data types.


The APL64-compatible data types are Boolean, Double, Int32, Char, Varchar and String.

The result is an APL 2-column matrix with one row for each out and inout parameter:

- Column #1: Parameter name
- Column #2: Parameter value

In and Out parameters with the In parameter specified before the Out parameter:

```
□sqlmyself←'#'□sqlmy 'Create' 'S1'  
cstr←"server=localhost;port=3306;database=schema1;userid=root;password=Ezalb"  
□sqlmy 'Open' cstr  
□dr"□←□SQLMY 'ExecStoredProc' 'spGetCompensationFromName' 'NameMatch, Comp' (1p<'Jim')
```



In and Out parameters with Out parameter specified before the In parameter:

```
□sqlmyself←'#'□sqlmy 'Create' 'S1'  
cstr←"server=localhost;port=3306;database=schema1;userid=root;password=Ezalb"  
□sqlmy 'Open' cstr  
□dr"□←□SQLMY 'ExecStoredProc' 'spGetCompensationFromName' 'Comp, NameMatch' (1p<'Jim')
```




The stored procedure definition:

```
Name: spGetCompensationFromName  
DDL:  
1 • CREATE DEFINER='root'@'localhost' PROCEDURE `spGetCompensationFromName` (IN NameMatch VARCHAR(45), OUT COMP DOUBLE)  
2 BEGIN  
3 SELECT Compensation INTO COMP FROM tbone WHERE Name=NameMatch;  
4 END
```

## ExecStoredProcCmd

This action can be used to run a stored procedure which has no input or output parameters. The single action argument is an APL text vector (cmdText) containing the stored procedure name. The result is an empty, 2-column APL matrix.

```
'#'  
sqlmy 'Clear'  
sqlmyself←'#'  
sqlmy 'Create' 'S1'  
cstr←"server=localhost;port=3306;database=schema1;userid=root;password=Ezalb"  
sqlmy 'Open' cstr  
ρ←SQLMY 'ExecStoredProcCmd' 'StoredProc1'  
SQLMY 'ExecSelectQuery' "Select Name From tbone Where Id=3"  
SQLMY 'GetRecord' 102  
sqlmy 'Open' cstr  
SQLMY 'Exec' 'Delete From tbone Where Id=3;'
```



```
APL64: CLEAR WS  
File Edit Session Objects Tools Options Help  
0 '#'  
1 sqlmyself←'#'  
2 sqlmy 'Create' 'S1'  
3 cstr←"server=localhost;port=3306;database=schema1;userid=root;password=Ezalb"  
4 sqlmy 'Open' cstr  
5 ρ←SQLMY 'ExecStoredProcCmd' 'StoredProc1'  
6 SQLMY 'ExecSelectQuery' "Select Name From tbone Where Id=3"  
7 SQLMY 'GetRecord' 102  
8 sqlmy 'Open' cstr  
9 SQLMY 'Exec' 'Delete From tbone Where Id=3;'  
10 0 0  
11 102  
12 Salmon  
13 1  
14  
Ready | Hist: Ln: 7 Col: 24 | Ins | Classic | Num | EN_US
```

## GetAllRecords

This action applies to an SQLMY instance. The 'GetAllRecords' action will get the remaining records which have not already been read from the specified record set. This action closes the specified record set, because all records have been read.

An exception may occur if the data in the record set has no representation in APL64. In this case the query which created the record set must be modified, e.g. Cast(), to make the returned data conformable with APL64.

An exception will occur if there are no remaining records to be read.

```
sqlmyself←'#'  
sqlmy 'Create' 'S1'  
cstr←"server=localhost;port=3306;database=schema1;userid=root;password=Ezalb"  
sqlmy 'Open' cstr  
SQLMY 'ExecSelectQuery' 'Select Name,Compensation From tbone;'  
ρ←results←SQLMY 'GetAllRecords' 102  
ρ←results←SQLMY 'GetAllRecords' 102
```

```

APL64: CLEAR WS
File Edit Session Objects Tools Options Help
[Icons]
0 [sqlmyself←'#'[sqlmy 'Create' 'S1'
1   cstr←"server=localhost;port=3306;database=schema1;userid=root;password=Ezalb"
2   [sqlmy 'Open' cstr
3   [SQLMY 'ExecSelectQuery' 'Select Name,Compensation From tbone;'
4   p[←results←[SQLMY 'GetAllRecords' 102
5   p[←results←[SQLMY 'GetAllRecords' 102
6 102
7   Joe 50000
8   Jim 60000
9 2 2
10 Record Set Id: 102 is closed.
11 [imm:6] p[←results←[SQLMY 'GetAllRecords' 102
12
13
Ready | Hist: Ln: 13 Col: 6 | Ins | Classic | Num | EN_US

```

```

[sqlmyself←'#'[sqlmy 'Create' 'S1'
cstr←"server=localhost;port=3306;database=schema1;userid=root;password=Ezalb"
[sqlmy 'Open' cstr
[SQLMY 'ExecSelectQuery' 'Select Id, DOB, Name,Compensation From tbone;'
p[←results←[SQLMY 'GetAllRecords' 102

```

```

APL64: CLEAR WS
File Edit Session Objects Tools Options Help
[Icons]
0 [sqlmyself←'#'[sqlmy 'Create' 'S1'
1   cstr←"server=localhost;port=3306;database=schema1;userid=root;password=Ezalb"
2   [sqlmy 'Open' cstr
3   [SQLMY 'ExecSelectQuery' 'Select Id, DOB, Name,Compensation From tbone;'
4   p[←results←[SQLMY 'GetAllRecords' 102
5 102
6 1 1/1/1960 12:00:00 AM Joe 50000
7 2 1/1/1961 12:00:00 AM Jim 60000
8 2 4
9 |
Ready | Hist: Ln: 9 Col: 6 | Ins | Classic | Num | EN_US

```

### GetConnectionState


This action applies to an [SQLMY instance. The result of the GetConnectionState action is a text vector indicating the connection state of the specified [SQLMY instance to an MySql database.

```

[sqlmyself←'#'[sqlmy 'Create' 'S1'

```


```
cstr←"server=localhost;port=3306;database=schema1;userid=root;password=Ezalb"  
sqlmy 'Open' cstr  
SQLMY 'GetConnectionState'  
SQLMY 'GetConnectionString'
```



## GetConnectionString

This action applies to an SQLMY instance. The result of the GetConnectionString is the MySQL connection string, if any, associated with the specified SQLMY instance. Use the Open action to set the connection string.

```
sqlmyself←'#' sqlmy 'Create' 'S1'  
cstr←"server=localhost;port=3306;database=schema1;userid=root;password=Ezalb"  
sqlmy 'Open' cstr  
SQLMY 'GetConnectionState'  
SQLMY 'GetConnectionString'
```




## GetRecord

This action applies to an `SQLMY` instance. The right argument is the `SQLMY` record set number. The `GetRecord` action will read the next available record, if any, from the specified record set and return its values to the APL64 instance.

An exception may occur if the data in the record set has no representation in APL64. In this case, the query which created the record set must be modified to make the returned data conformable with APL64. If such an exception does occur, the `Cast()` method of the database can generally convert the source data in the database record to an APL64 data type.

```
SQLMYSELF←'#'SQLMY 'Create' 'S1'  
cstr←"server=localhost;port=3306;database=schema1;userid=root;password=Ezalb"  
SQLMY 'Open' cstr  
SQLMY 'ExecSelectQuery' 'Select * From tbone Where Id=2;'  
ρ←result←SQLMY 'GetRecord' 102
```



```
APL64: CLEAR WS  
0 SQLMYSELF←'#'SQLMY 'Create' 'S1'  
1 cstr←"server=localhost;port=3306;database=schema1;userid=root;password=Ezalb"  
2 SQLMY 'Open' cstr  
3 SQLMY 'ExecSelectQuery' 'Select * From tbone Where Id=2;'  
4 ρ←result←SQLMY 'GetRecord' 102  
5 102  
6 2 Jim 1/1/1961 12:00:00 AM 60000  
7 1 4  
8
```

## GroupSeparator

This action returns the [.Net Number Group Separator](#) text applicable to the specified `SQLMY` instance.

```
SQLMYSELF←'#'SQLMY 'Create' 'S'  
SQLMY 'DateFormat'  
SQLMY 'DecimalSeparator'  
SQLMY 'GroupSeparator'
```

```

APL64: CLEAR WS
File Edit Session Objects Tools Options Help
0      []SQLMYSelf←'#'[]SQLMY 'Create' 'S'
1      []SQLMY 'DateFormat'
2      M/d/yyyy
3      []SQLMY 'DecimalSeparator'
4      .
5      []SQLMY 'GroupSeparator'
6      ,
7
Ready | Hist: Ln: 7 Col: 6 Ins Classic Num EN_US

```

? or Help

This action is performed on the []SQLMY object. The ? and Help actions will return a text array containing a summary of the []SQLMY syntax.

```


APL64: CLEAR WS
File Edit Session Objects Tools Options Help
0      []SQLMY '?'
1      []SQLMY Summary Documentation
2          instanceName []SQLMY 'BeginTransaction'
3          '#' []SQLMY 'Clear'
4          instanceName []SQLMY 'Close'
5          instanceName []SQLMY 'CommitTransaction'
6      char[]          +instanceName []SQLMY 'GetConnectionState'
7      connString     +instanceName []SQLMY 'GetConnectionString'
8      Int32          + '#' []SQLMY 'Count'
9      instanceName   + '#' []SQLMY 'Create' instanceName
10     dateFormat     +instanceName []SQLMY 'DateFormat'
11     1 1p«DBNull»   + '#' []SQLMY 'DBNull'
12     decimalSeparator +instanceName []SQLMY 'DecimalSeparator'
13     instanceName   []SQLMY 'Delete'
14     Int32(rcdSetId) +instanceName []SQLMY 'Exec cmdText(Not a query)'
15     Int32          +instanceName []SQLMY 'ExecDeleteQuery' cmdText
16     instanceName   []SQLMY 'ExecInsertQuery' tableName fieldNames data
17     Int32(rcdSetId) +instanceName []SQLMY 'ExecSelectQuery' cmdText
18     matrix of values +instanceName []SQLMY 'ExecStoredProc' cmdText fieldNames dataVector
19     matrix of values +instanceName []SQLMY 'ExecStoredProcCmd' cmdText
20     matrix of values +instanceName []SQLMY 'GetAllRecords Int32(rcdSetId)'
21     vector of values +instanceName []SQLMY 'GetRecord Int32(rcdSetId)'
22     groupSeparator +instanceName []SQLMY 'GroupSeparator'
23     charVec        + '#' []SQLMY '?'
24     charVec        + '#' []SQLMY 'Help'
25     vector of char vectors + '#' []SQLMY 'Instances'
26     bool           +instanceName []SQLMY 'InTransaction'
27     charVec        +instanceName []SQLMY 'New'
28     instanceName   []SQLMY 'Open' connString
29     instanceName   []SQLMY 'RegionalSettings' dateFormat decimalSeparator numberGroup
30     instanceName   []SQLMY 'RollbackTransaction'
31     charVec        +instanceName []SQLMY 'Self'
32
33
Ready | Hist: Ln: 33 Col: 6 Ins Classic Num EN_US

```

## Instances

This action is performed on the `SQLMY` object. The result of the Instances action is the number of existing `SQLMY` instances in the APL64 instance.

```
'# SQLMY 'Clear'  
ρ←'# SQLMY 'instances'  
'# SQLMY 'Create' 'A'  
'# SQLMY 'Create' 'B'  
ρ←'# SQLMY 'instances'
```




```
APL64: CLEAR WS  
File Edit Session Objects Tools Options Help  
0 '# SQLMY 'Clear'  
1 ρ←'# SQLMY 'instances'  
2 '# SQLMY 'Create' 'A'  
3 '# SQLMY 'Create' 'B'  
4 ρ←'# SQLMY 'instances'  
5 0  
6 A  
7 B  
8 A B  
9 2  
10  
Ready | Hist: Ln: 10 Col: 6 | Ins | Classic | Num | EN_US
```

## InTransaction

This action applies to an `SQLMY` instance. The Boolean result of the InTransaction action indicates if a transaction block is in existence for the specified `SQLMY` instance.

```
'# sqlmy 'Clear'  
sqlmyself←'# sqlmy 'Create' 'S1'  
cstr←"server=localhost;port=3306;database=schema1;userid=root;password=Ezalb"  
sqlmy 'Open' cstr  
SQLMY 'RollbackTransaction'  
SQLMY 'InTransaction'
```




```
APL64: CLEAR WS  
File Edit Session Objects Tools Options Help  
0 '# sqlmy 'Clear'  
1 sqlmyself←'# sqlmy 'Create' 'S1'  
2 cstr←"server=localhost;port=3306;database=schema1;userid=root;password=Ezalb"  
3 sqlmy 'Open' cstr  
4 SQLMY 'RollbackTransaction'  
5 SQLMY 'InTransaction'  
6 0  
7  
Ready | Hist: Ln: 7 Col: 6 | Ins | Classic | Num | EN_US
```

## New

This action is performed on the `SQLMY` object. The New action will create an `SQLMY` instance with a user-provided name in the right argument. Multiple `SQLMY` instances are possible in the same APL64 instance, so that multiple MySQL databases may be conveniently accessed. The New action will fail if the named instance already exists. The New action for a particular MySQL database is generally used once in an APL64 instance. The New action does not open a connection to an MySQL database, use the Open action for that purpose. The result of a successful 'New' action is a text vector containing the `SQLMY` instance name.

```
'#SQLMY 'Clear'  
'#SQLMY 'New' 'instance1'  
'#SQLMY 'New' 'instance1'
```




```
APL64: CLEAR WS  
File Edit Session Objects Tools Options Help  
0 '#SQLMY 'Clear'  
1 '#SQLMY 'New' 'instance1'  
2 '#SQLMY 'New' 'instance1'  
3 instance1  
4 DOMAIN ERROR: SQLMY: SqliteInstance: instance1 already exists  
5 [imm:3] '#SQLMY 'New' 'instance1'  
6 ^  
7
```

## Open

This action applies to an `SQLMY` instance. The Open action requires the specification of a [connection string](#) as the right argument.

```
sqlmyself←'#sqlmy 'Create' 'S1'  
cstr←"server=localhost;port=3306;database=schema1;userid=root;password=Ezalb"  
sqlmy 'Open' cstr  
SQLMY 'GetConnectionState'  
SQLMY 'GetConnectionString'
```




### RegionalSettings

- This action can be used to set the regional values for the specified SQLMY instance:
- ShortDatePattern
- CurrencyDecimalSeparator, NumberDecimalSeparator & PercentDecimalSeparator
- CurrencyGroupSeparator, NumberGroupSeparator & PercentGroupSeparator

```

SQLMYSelf←'#'[]SQLMY 'Create' 'S'
SQLMY 'RegionalSettings' 'M/d/yyyy' '!' ','

```



### RollbackTransaction

This action applies to an SQLMY instance. The RollbackTransaction action is used to cancel any pending SQL operations which are included in the current SQL transaction. The RollbackTransaction action has no result. The RollbackTransaction action has no effect if no SQL transaction is in progress.

```

sqlmyself←'#'[]sqlmy 'Create' 'S1'
cstr←"server=localhost;port=3306;database=schema1;userid=root;password=Ezalb"
sqlmy 'Open' cstr
SQLMY 'RollbackTransaction'

```

```

APL64: CLEAR WS
File Edit Session Objects Tools Options Help
0      []sqlmyself←'#'[]sqlmy 'Create' 'S1'
1      cstr←"server=localhost;port=3306;database=schema1;userid=root;password=Ezalb"
2      []sqlmy 'Open' cstr
3      []SQLMY 'RollbackTransaction'
4      |

```

Ready | Hist: Ln: 4 Col: 6 | Ins | Classic | Num | EN\_US

```

[]sqlmyself←'#'[]sqlmy 'Create' 'S1'
cstr←"server=localhost;port=3306;database=schema1;userid=root;password=Ezalb"
[]sqlmy 'Open' cstr
[]SQLMY 'RollbackTransaction'
[]SQLMY 'ExecSelectQuery' 'Select Name from tbone;'
[]SQLMY 'GetAllRecords' 102
[]SQLMY 'BeginTransaction'
[]SQLMY 'ExecInsertQuery' 'tbone' 'Id,Name,DOB,Compensation' (3 'Salmon' '1966-01-01' 90500.56)
[]SQLMY 'RollbackTransaction'
[]SQLMY 'ExecSelectQuery' 'Select Name from tbone;'
[]SQLMY 'GetAllRecords' 103

```

```

APL64: CLEAR WS
File Edit Session Objects Tools Options Help
0      []sqlmyself←'#'[]sqlmy 'Create' 'S1'
1      cstr←"server=localhost;port=3306;database=schema1;userid=root;password=Ezalb"
2      []sqlmy 'Open' cstr
3      []SQLMY 'RollbackTransaction'
4      []SQLMY 'ExecSelectQuery' 'Select Name from tbone;'
5      []SQLMY 'GetAllRecords' 102
6      []SQLMY 'BeginTransaction'
7      []SQLMY 'ExecInsertQuery' 'tbone' 'Id,Name,DOB,Compensation' (3 'Salmon' '1966-01-01' 90500.56)
8      []SQLMY 'RollbackTransaction'
9      []SQLMY 'ExecSelectQuery' 'Select Name from tbone;'
10     []SQLMY 'GetAllRecords' 103
11     102
12     Joe
13     Jim
14     103
15     Joe
16     Jim
17     |

```

Ready | Hist: Ln: 17 Col: 6 | Ins | Classic | Num | EN\_US

```

[]sqlmyself←'#'[]sqlmy 'Create' 'S1'
cstr←"server=localhost;port=3306;database=schema1;userid=root;password=Ezalb"
[]sqlmy 'Open' cstr
[]SQLMY 'RollbackTransaction'
[]SQLMY 'ExecSelectQuery' 'Select Name from tbone;'
[]SQLMY 'GetAllRecords' 102
[]SQLMY 'BeginTransaction'

```

- SQLMY 'ExecInsertQuery' 'tbone' 'Id,Name,DOB,Compensation' (3 'Salmon' '1966-01-01' 90500.56)
- SQLMY 'ExecSelectQuery' 'Select Name from tbone;'
- SQLMY 'GetAllRecords' 103
- SQLMY 'RollbackTransaction'
- SQLMY 'ExecSelectQuery' 'Select Name from tbone;'
- SQLMY 'GetAllRecords' 104

Note that the records in the #103 data set include the pending effects of the ExecInsertQuery action, but the records in the #104 data set do not include the effects of the rolled back ExecInsertQuery action:

```

0      □sqlmyself+'#'□sqlmy 'Create' 'S1'
1      cstr←"server=localhost;port=3306;database=schema1;userid=root;password=Ezalb"
2      □sqlmy 'Open' cstr
3      □SQLMY 'RollbackTransaction'
4      □SQLMY 'ExecSelectQuery' 'Select Name from tbone;'
5      □SQLMY 'GetAllRecords' 102
6      □SQLMY 'BeginTransaction'
7      □SQLMY 'ExecInsertQuery' 'tbone' 'Id,Name,DOB,Compensation' (3 'Salmon' '1966-01-01' 90500.56)
8      □SQLMY 'ExecSelectQuery' 'Select Name from tbone;'
9      □SQLMY 'GetAllRecords' 103
10     □SQLMY 'RollbackTransaction'
11     □SQLMY 'ExecSelectQuery' 'Select Name from tbone;'
12     □SQLMY 'GetAllRecords' 104
13     102
14     Joe
15     Jim
16     103
17     Joe
18     Jim
19     Salmon
20     104
21     Joe
22     Jim
23

```


### Self

This action is performed on the  SQLMY object. The right argument specifies an  SQLMY instance name for a potentially existing  SQLMY instance. If the  SQLMY instance exists in the APL64 instance, the result of the Self action is the  SQLMY instance name.

```

'#'□SQLMY 'Create' 'instance1'
ρ□←'instance1'□SQLMY           'Self'
'#'□SQLMY 'Clear'
ρ□←'instance1'□SQLMY 'Self'

```



The screenshot shows a window titled "APL64: CLEAR WS" with a menu bar (File, Edit, Session, Objects, Tools, Options, Help) and a toolbar. The main area contains the following text:

```
0      '#\SQLMY 'Create' 'instance1'  
1      ρ\+'instance1'\SQLMY 'Self'  
2      '#\SQLMY 'Clear'  
3      ρ\+'instance1'\SQLMY 'Self'  
4 instance1  
5 instance1  
6 9  
7  
8 0  
9 |
```

At the bottom, a status bar shows "Ready" on the left and "Hist: Ln: 9 Col: 6 Ins | Classic | Num | EN\_US" on the right.

## Learn Structured Query Language

<http://www.w3schools.com/sql/default.asp>